

## SPECIAL ADDITIONAL FEATURES FOR 1800 RPM, SENTRY-PRO POWER PLANTS

PART #	PART	DESCRIPTION FOR ITEMS, USED WITH ONLY 4-POLE 1800 RPM STANDBY SETS	
S-8A	EXTERNAL PMG EXCITATION	25 THRU 400 KW, IMPROVING MOTOR STARTING CAPABILITIES AND UN-INTERRUPTED EXCITATION POWER.	
S-8B	EXTERNAL PMG EXCITATION WITH DIGITAL VOLTAGE REGULATOR	25 THRU 400 KW, IMPROVING MOTOR STARTING CAPABILITIES, UN-INTERRUPTED EXCITATION POWER AND RMS SENSING. STANDARD ON 425 THRU 800 KW.	
S-10A	1" FLEXIBLE DRY FUEL LINE	LPG OR NATURAL GAS LINE WITH 1" NPT FITTINGS, 12" LONG FOR 25-60 KW.	
S-10B	1-1/4" FLEXIBLE DRY FUEL LINE	LPG OR NATURAL GAS LINE WITH 1-1/4" NPT FITTINGS, 12" LONG FOR 80-150 KW.	
S-10C	2" FLEXIBLE DRY FUEL LINE	LPG OR NATURAL GAS LINE WITH 2" NPT FITTINGS, 14" LONG FOR 180-425 KW.	
S-13C	1000 WATT ENGINE COOLANT HEATER	COOLANT HEATER WITH ON-OFF THERMOSTAT. USE THIS 1000 WATT HEATER ON 25 THRU 62 KW SETS.	
S-13D	1500 WATT ENGINE COOLANT HEATER	COOLANT HEATER WITH ON-OFF THERMOSTAT. USE THIS 1500 WATT HEATER ON 80-150 KW DRY FUEL AND 80-210 KW DIESEL FUEL SETS.	
S-13E	2000 WATT ENGINE COOLANT HEATER	COOLANT HEATER WITH ON-OFF THERMOSTAT. USE 2000 WATT HEATER ON 180-200 KW DRY FUEL AND 250-300 KW DIESEL FUEL SETS.	
S-13F	INLET/OUTLET VALVE SYSTEMS FOR HEATER REPLACEMENT	TWO BRASS VALVES FOR INLET/OUTLET PIPES LEADING TO COOLANT HEATER FOR EASE OF POSSIBLE HEATER REPLACEMENT.	
S-13G	5000 WATT ENGINE COOLANT HEATER	5,000 WATT, COOLANT HEATER WITH ON-OFF THERMOSTAT.	DRY FUEL 265-425 KW
			DIESEL 350-800 KW
S-14	BATTERY HEATER	50 WATT HEATER BLANKET THAT WRAPS AROUND BATTERY, WITH ON-OFF THERMOSTAT.	
S-16A	10 AMP BATTERY CHARGER	NRG, BATTERY CHARGER (25 THRU 600 KW GEN-SETS), PROGRAMMABLE CHARGER WITH LOW RIPPLE FLOAT CHARGING AT 12 VDC, OR 24 VDC, MULTI-STAGE (FLOAT, BULK, ABSORPTION, AND AUTO-BOOST), TEMPERATURE COMPENSATION, NFPA-110 ALARM TRIGGER FOR: AC FAILURE, CHARGE FAILURE, HIGH OR LOW BATTERY VOLTS, LCD READOUT FOR DC VOLTS AND LAMPS, PLUS STAINLESS STEEL HOUSING FOR WALL MOUNT	
S-16D	20 AMP BATTERY CHARGER		

## SPECIAL ADDITIONAL FEATURES FOR 1800 RPM, SENTRY-PRO POWER PLANTS

PART #	PART	DESCRIPTION FOR ITEMS, USED WITH ONLY 4-POLE 1800 RPM STANDBY SETS	
S-B600	600 CCA STARTING BATTERY 12VDC	12 VDC STARTING BATTERY RATED 600 CCA	25-60KW
S-B750	750 CCA STARTING BATTERY 12VDC	12 VDC STARTING BATTERY RATED 750 CCA	GAS 80-150KW DIESEL 80-210KW
(2)S-B1000	(2) 1000 CCA STARTING BATTERIES 24VDC	(2) 12 VDC STARTING BATTERIES (24 VDC STARTING SYSTEM) RATED 1000 CCA EACH	GAS 200-650KW DIESEL 250-800KW
S-17B	EMERGENCY STOP SWITCH WITH (1) N. O. CONTACT BLOCK	"MUSHROOM" STYLE STOP SWITCH MOUNTED IN NEMA-4X SMALL ENCLOSURE, UL LISTED, SUITABLE FOR REMOTE LOCATIONS, COMPLIES WITH NFPA-110 REQUIREMENTS.	
S-17C	EMERGENCY STOP SWITCH WITH (1) N. O. CONTACT BLOCK	"MUSHROOM" STYLE STOP SWITCH MOUNTED IN "BREAK GLASS STATION" NEMA-3R SMALL ENCLOSURE, UL LISTED, SUITABLE FOR REMOTE LOCATIONS, COMPLIES WITH NFPA-110 REQUIREMENTS.	
S-39	GENERATOR ENCLOSURE LIGHTS	12/24 VDC POWERED INTERIOR ENCLOSURE (2)LIGHTS FOR 25 THRU 62 KW AND (4) LIGHTS FOR 80 THRU 800 KW.	25-800 KW
S-39T	GENERATOR ENCLOSURE LIGHTS WITH 15 MIN TIMER	12/24 VDC POWERED INTERIOR ENCLOSURE LIGHTS INCLUDES ROTARY DIAL 15 MIN. TIMER	25-800 KW
S-39AC	AC GENERATOR ENCLOSURE LIGHTS	120/240 VAC POWERED INTERIOR ENCLOSURE LIGHT (ELECTRICAL CONTRACTOR TO SUPPLY LOAD WIRES THAT ARE CIRCUIT PROTECTED FROM THE BUILDING	25-800 KW
S-40	LIQUID LP FUEL SYSTEM	COMPLETE LIQUID LP CARBURETION SYSTEM, INSTALLED ON 25-150 KW GEN-SETS.	
S-41A	DUAL FUEL (LPG/NG) AUTOMATIC FUEL SWITCHING	AS ONE DRY FUEL SOURCE ENDS, THE SECOND CONNECTED DRY FUEL SOURCE AUTOMATICALLY CONTINUES NONSTOP OPERATION FOR 25 THRU 150 KW. (NOT AVAILABLE WHEN USING S-40 LIQUID LP SYSTEM)	
S-50A	EXTENDED WARRANTY	5 YEAR EXTENDED WARRANTY FOR 25-60 KW STANDBY	
S-50B		5 YEAR EXTENDED WARRANTY FOR 80-210 KW STANDBY	
S-50C		5 YEAR EXTENDED WARRANTY FOR 250-800 KW STANDBY	
S-51A	FRAME BASE DRIP PAN	LIQUID CONTAINMENT PAN INSTALLED UNDER FRAME BASE. 25-60 KW	
S-51B		LIQUID CONTAINMENT PAN INSTALLED UNDER FRAME BASE. 80-150 KW	
S-51C		LIQUID CONTAINMENT PAN INSTALLED UNDER FRAME BASE. 200-350 KW	
S-51D		LIQUID CONTAINMENT PAN INSTALLED UNDER FRAME BASE. 400-800 KW	

## SPECIAL ADDITIONAL FEATURES FOR 1800 RPM, SENTRY-PRO POWER PLANTS

PART #	PART	DESCRIPTION FOR ITEMS, USED WITH ONLY 4-POLE 1800 RPM STANDBY SETS	
S-52A	SEQ SPRING VIBRATION MOUNTS	WITH RESTRAINTS FOR 25-62 KW, QUANTITY OF 4	
S-52B		WITH RESTRAINTS FOR 75-210 KW, QUANTITY OF 6	
S-52C		WITH RESTRAINTS FOR 265-300 KW GAS, 250-500 KW DIESEL QUANTITY OF 8	
S-52D		WITH RESTRAINTS FOR 350-425 KW GAS, 550-800 KW DIESEL QUANTITY OF 10	
S-77B	PARALLELING PACKAGE	PARALLELING PACKAGE BUILT WITH ABB MOTORIZED CIRCUIT BREAKER & BASLER 2020HD SYNCRONIZING CONTROLLER	200-800 KW
S-78A	LOAD CENTER	AUXILIARY CONNECTION BOX FRAME MOUNTED. 120/240V 1PH TERMINAL STRIPS ONLY FOR BLOCK HEATER & BATTERY CHARGER CONNECTIONS. ELECTRICAL CONTRACTOR TO SUPPLY LOAD WIRES THAT ARE CIRCUIT PROTECTED FROM THE BUILDING.	25-800 KW
S-MD24	MOTORIZED DAMPERS	24 X 24 HEAVY DUTY 120-240 VAC MOTORIZED DAMPERS	25-60 KW
S-MD36		36 X 36 HEAVY DUTY 120-240 VAC MOTORIZED DAMPERS	80-150 KW
S-MD42		42 X 42 HEAVY DUTY 120-240 VAC MOTORIZED DAMPERS	DIESEL 250-300 KW
S-MD48		48 X 48 HEAVY DUTY 120-240 VAC MOTORIZED DAMPERS	GAS 200-425 KW DIESEL 350-800 KW
S-SW1	VOLTAGE SELECTOR SWITCH	MODULAR DESIGN ROTARY CAM FOR SWITCHABLE VOLTAGES; 208/480 VOLT 3 PHASE AND 120/240 VOLT 1 PHASE.	25-40 KW
S-SW2			55-80 KW
S-SW3		ONE MAINLINE CIRCUIT BREAKER PROVIDED FOR ALL VOLTAGES.	100-150 KW
S-112A	ENCLOSURE DOOR RESTRAINTS	MAGNETIC DOOR RESTRAINTS TO HOLD DOOR OPEN DURING SERVICE.	25-210 KW
S-112B			250-800 KW
S-114A	ISOLATOR MOUNTINGS PADS	3' X 6" X 1/4" THICK ANTI-VIBRATION PADS, QTY 4	25-210 KW
S-114B		3' X 6" X 1/4" THICK ANTI-VIBRATION PADS, QTY 8	250-500 KW
S-114C		3' X 6" X 1/4" THICK ANTI-VIBRATION PADS, QTY 10	550-800 KW
S-EH3	ENCLOSURE SPACE HEATER	3 KW, 1 PHASE OR 3 PHASE HEATER WITH THERMOSTAT	25-210 KW
S-EH5		5 KW, 1 PHASE OR 3 PHASE HEATER WITH THERMOSTAT	250-800 KW