



# GILLETTE GENERATORS

## LIQUID COOLED DIESEL ENGINE GENERATOR SET

60 HZ MODEL  
**T4D-3000**

Model	HZ	STANDBY	PRIME
		130°C RISE	105°C RISE
<b>T4D-3000-60 HERTZ</b>	60	300	300



All generator sets are USA prototype built and thoroughly tested. Production models are USA factory built and 100% load tested.



**UL1446, UL508, UL142, UL498**



**NFPA 110, 99, 70, 37**

All generator sets meet NFPA-110 Level 1, when equipped with the necessary accessories and installed per NFPA standards.



**NEC 700, 701, 702, 708**



**NEMA ICS10, MG1, ICS6, AB1**



**ANSI C62.41, 27, 59, 32, 480, 40Q, 81U, 360-05**




**ASCE 7-05 & 7-10**

All generator sets meet 180 MPH rating.




**EPA 40CFR Part 60, 89, 1039, 1048, 1054, 1065, 1068**



“OPEN” GEN-SET

There is no enclosure, so gen-set must be placed within a weather protected area, uninhabited by humans or animals, with proper ventilation. Silencer not supplied, as installation requirements are not known. However, this item is available as optional equipment.



“LEVEL 2” HOUSED GEN-SET

Full aluminum weather protection and superior sound attenuation for specific low noise applications. Critical grade muffler is standard.

### GENERATOR RATINGS

GENERATOR MODEL	VOLTAGE		PH	HZ	130°C RISE STANDBY RATING		105°C RISE PRIME RATING	
	L-N	L-L			KW/KVA	AMP	KW/KVA	AMP
<b>T4D-3000-3-2</b>	120	208	3	60	300/375	1042	300/375	1042
<b>T4D-3000-3-3</b>	120	240	3	60	300/375	903	300/375	903
<b>T4D-3000-3-4</b>	277	480	3	60	300/375	451	300/375	451
<b>T4D-3000-3-5</b>	127	220	3	60	300/375	985	300/375	985
<b>T4D-3000-3-16</b>	346	600	3	60	300/375	361	300/375	361

RATINGS: All three phase gen-sets are 12 lead windings, rated at .8 power factor. 130° C “STANDBY RATINGS” are strictly for gen-sets that are used for back-up emergency power to a failed normal utility power source. This standby rating allows varying loads, with no overload capability, for the entire duration of utility power outage. 105° C “PRIME RATINGS” are strictly for gen-sets that provide the prime source of electric power, where normal utility power is unavailable or unreliable. A 10% overload is allowed for a total of 1 hour, within every 12 hours of operation, on every PRIME RATED systems. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based 130°C (standby), and 105°C (prime) R/R winding temperature, within a maximum 40°C ambient condition. Generators operated at standby power ratings must not exceed the temperature rise limitation for class H insulation system, as specified in NEMA MG1-22.40. Specifications & ratings are subject to change without prior notice.

# APPLICATION & ENGINEERING DATA FOR MODEL T4D-3000-60 HZ

## GENERATOR SPECIFICATIONS

Manufacturer..... Stamford Generators  
Model & Type..... S4L1D-F311, 4 Pole, 12 Lead, Three Phase  
.....S4L1D-E311, 4 Pole, 12 Lead, 480V, Three Phase  
.....S4L1S-E17, 4 Pole, 12 Lead, 600V, Three Phase  
Exciter..... Brushless, shunt excited  
Voltage Regulator..... Solid State, HZ/Volts  
Voltage Regulation..... ½%, No load to full load  
Frequency..... Field convertible, 60 HZ to 50 HZ  
Frequency Regulation..... ± ½% (1/2 cycle, no load to full load)  
Unbalanced Load Capability..... 100% of standby amps  
One Step Load Acceptance..... 100% of nameplate rating  
Total Stator and Load Insulation..... Class H, 180°C  
Temperature Rise..... 105°C R/R, prime rating @ 40°C amb.  
3 Ø Motor Starting @ 30% Voltage Dip (208-240V)... 1500 kVA  
3 Ø Motor Starting @ 30% Voltage Dip (480V-600V) 2300 kVA  
Bearing..... 1, Pre-lubed and sealed  
Coupling..... Direct flexible disc.  
Total Harmonic Distortion..... Max 3½% (MIL-STD705B)  
Telephone Interference Factor..... Max 50 (NEMA MG1-22)  
Deviation Factor..... Max 5% (MIL-STD 405B)  
Alternator..... Self ventilating and drip-proof  
Ltd. Warranty Period..... 24 Months from start-up date or  
..... 1000 hours use, first to occur.

## GENERATOR FEATURES

- World Renown Stamford Electric Generator having UL-1446 certification.
- Full generator protection with **Deep Sea 7420** controller, having UL-508 certification.
- Automatic voltage regulator with over-excitation, under-frequency compensation, under-speed protection, and EMI filtering. Entire solid-state board is encapsulated for moisture protection.
- Generator power ratings are based on temperature rise, measured by resistance method, as defined in MIL-STD 705C and IEEE STD 115, Method 6.4.4.
- Power ratings will not exceed temperature rise limitation for class H insulation as per NEMA MG1-22.40.
- Insulation resistance to ground, exceeds 1.5 meg-ohm.
- Stator receives 2000 V. hi-potential test on main windings, and rotor windings receive a 1500 V. hi-potential test, as per MIL-STD 705B.
- Full amortisseur windings with UL-1446 certification.
- Complete engine-generator torsional acceptance, confirmed during initial prototype testing.
- Full load testing on all engine-generator sets, before shipping.

## ENGINE SPECIFICATIONS AND APPLICATIONS DATA

### ENGINE

Manufacturer..... VOLVO-PENTA  
Model and Type..... TAD1373VE, 4 cycle, liquid Cooled  
Aspiration..... Turbo After Cooler, H2O to Air  
Charged Air Cooled System..... H2O to Air  
Cylinder Arrangement..... 6 Cylinders, In-Line  
Displacement Cu. In. (Liters)..... 780 (12.8)  
Bore & Stroke in (Cm)..... 5.16 x 6.22 (13.1 x 15.8)  
Compression Ratio..... 17.8:1  
Main Bearings..... Tin Overlay with Babbit Backing  
Cylinder Head..... Cast Iron with overhead Cam  
Pistons..... Aluminum Alloy with Graphite Coating  
Crankshaft..... Induction Hardened, Heat Treated Forged  
Valves..... Heat Treated and Hardened Exhaust Valve  
Governor..... Electronic, EMS 2.2  
Frequency Regulation..... ± 1/4%  
Air Cleaner..... Dry, Replaceable Cartridge  
Engine Speed..... 1800 rpm  
Max Power, bhp (kwm) Standby..... 469 (345)  
BMEP: psi (MPa) Standby..... 340 (2.3)  
Ltd. Warranty Period..... 2 Year or 1000 hrs, first to occur

### FUEL SYSTEM

Type..... Diesel Fuel Oil (ASTM No. 2-D)  
Combustion System..... Direct Injection  
Fuel Injection Pump..... Electronic, Delphi E3  
24 VDC Coolant heaters..... Optional Equipment  
Fuel Filter..... Yes with Water Separator

### FUEL CONSUMPTION

GAL/HR (LITER/HR)	STANDBY	PRIME
100% LOAD	21.8 (82.7)	21.8 (82.7)
75% LOAD	16.6 (62.7)	16.6 (62.7)
50% LOAD	11.5 (43.5)	11.5 (43.5)

### OIL SYSTEM

Type..... Full Pressure  
Oil Pan Capacity qt. (L)..... 31.6 (29.9)  
Oil Pan Cap. W/ filter qt. (L)..... 38 (35.9)  
Oil Filter..... 3, Replaceable Cartridge type

### ELECTRICAL SYSTEM

Ignition System..... Electronic  
Eng. Alternator/Starter: 24 VDC, negative ground, 110 amp/hr.  
Recommended battery to -18°C (0° F): ....(2) 12 VDC, BCI# 31,  
Max. Dimensions: 14"lg x 6 3/4" wi x 10" hi, with standard  
round posts. Min output 1000 CCA. Battery tray (max. dim. at  
15"lg x 7"wi). This model has (2) battery trays, (2) hold down  
straps, (2) sets of battery cables, and (1) battery charger.  
Installation of (2) 12VDC starting batteries connected in series  
for 24VDC output is required, with possible higher AMP/HR  
rating, as described above, if the normal environment  
temperature averages -13° F (-25°C) or cooler.

### CERTIFICATIONS

All engines are EPA emissions certified. All non-emergency  
stationary diesel engines are Tier IV Final compliant.

# APPLICATION & ENGINEERING DATA FOR MODEL T4D-3000-60 HZ

## COOLING SYSTEM

Type of System ..... Air to Air, Charged Air Cooler  
 Coolant Pump .....Pre-lubricated, self-sealing  
 Cooling Fan Type .....Pusher  
 Fan Diameter inches (cm).....35.1 (89)  
 Fan drive ratio..... 0.99:1  
 Ambient Capacity of Radiator °F (°C)..... 131 (55)  
 Engine Jacket Coolant Capacity gal. (L).....5.28 (20)  
 Radiator Coolant Capacity gal. (L) ..... 11.7 (44)  
 Water Pump Capacity gpm (L/min)..... 87.0 (329)  
 Heat Reject Coolant: Btu/min .....10,123  
 Air to Air Heat Reject, BTU/min. ....5,346  
 Heat Radiated to Ambient, BTU/min .....3,415  
 Low Radiator Coolant Level Shutdown.....Standard  
 Note: Coolant temp. shut-down switch setting at 228°F (109°C) with 50/50 (water/antifreeze) mix.

## COOLING AIR REQUIREMENTS

Combustion Air cfm (m<sup>3</sup>/min) ..... 1,646 (46.6)  
 Max Air Intake Restrictions:  
     Clean Air Cleaner, KPA (psi) ..... 5 (1.5)  
 Radiator Cooling Air, SCFM (m<sup>3</sup>/min).....29,894 (846)

## EXHAUST SYSTEM

Exhaust Outlet Size .....8"  
 Max. Back Pressure in KPA (in. H2O) ..... 10 (40)  
 Exhaust Flow, at rated KW, CFM (m<sup>3</sup>/min)..... 4,347 (123)  
 Exhaust Temp, (Stack) °F (°C) ..... 932 (500)

## SOUND LEVELS MEASURED IN dB(A)

	Open Set	Level 2 Encl.
Level 2, Critical Silencer .....	98	83
Level 3, Hospital Silencer.....	93	78

Note: Open sets (no enclosure) have optional silencer system choices due to unknown job-site applications. Level 2 enclosure has installed critical silencer with upgrade to Level 3 hospital silencer. Sound tests are averaged from several test points and taken at 23 ft. (7 m) from source of noise at normal operation.

## DERATE GENERATOR FOR ALTITUDE

3% per 1000 ft. (305m) above 3000 ft. (914m) from sea level

## DERATE GENERATOR FOR TEMPERATURE

2% per 10°F (5.6°C) above 104°F (40°C)

## DIMENSIONS AND WEIGHTS

	Open Set	Level 2 Enclosure
Length in (cm).....	132 (335)	186 (472)
Width in (cm).....	52 (132)	72 (183)
Height in (cm).....	65 (165)	94 (239)
Net Weight lbs (kg).....	6327 (2870)	8097 (3673)
Ship Weight lbs (kg).....	6602 (2995)	8462 (3839)

# DEEP SEA 7420 DIGITAL MICROPROCESSOR CONTROLLER



### Deep Sea 7420

The “7420” controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which continuously displays the status of the engine and generator at all times.

The “7420” controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs • (8) configurable outputs • voltage monitoring • mains (utility) failure detection • (250) event logs • configurable timers • automatic shutdown or warning during fault detection • remote start (on load) • engine preheat • advanced metering capability • hour meter • text LCD displays • protected solid state outputs • test buttons for: stop/reset • manual mode • auto mode • lamp test • start button • power monitoring (kWh, kVAr, kVAh, kVArh)

This controller includes expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSENet for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.



Further expansion is available by adding the optional “WebNet” gateway interface module. This device will allow comprehensive monitoring of the generator via the cloud including identification, location, and status. Some advantages of this module include: reduced site visits and maintenance costs • remote fuel management • fault analysis • asset tracking • automatic system alerts • maximized system up-time.

# STANDARD FEATURES FOR MODEL T4D-3000-60 HZ

## STANDARD FEATURES

### CONTROL PANEL:

- Deep Sea 7420 digital microprocessor with logic allows programming in the field. Controller has:
- STOP-MANUAL-AUTO modes and automatic engine shutdowns, signaled by full text LCD indicators:
  - Low oil pressure
  - High engine temp
  - Low Radiator Level
  - Three auxiliary alarms
  - Battery fail alarm
  - Engine fail to start
  - Engine over speed
  - Engine under speed
  - Over & under voltage

Also included is tamper-proof engine hour meter

### ENGINE:

- Fuel filter
- Full flow Oil filter
- Air filter
- Fuel pump
- Oil pump
- Solenoid type starter motor
- Hi-temp radiator
- Jacket water pump
- Thermostat
- Pusher fan and guard
- Exhaust manifold
- Electronic Governor
- 24 VDC battery charging alternator
- Flexible fuel and exhaust connectors
- Vibration isolators
- Open coolant recovery system with 50/50 water to anti-freeze mixture
- flexible oil & radiator hose
- Shut-down sensors for low oil pressure, high coolant temp., low coolant level, high ambient temp.

### AC GENERATOR SYSTEM:

- AC generator
- Shunt excited
- Brushless design
- Circuit Breaker installed and wired to gen-set
- Direct connection to engine with flex disc
- Class H, 180°C insulation
- Self ventilated
- Drip proof construction
- UL Certified

### VOLTAGE REGULATOR:

- 1% Voltage regulation
- EMI filter
- Under-speed protection
- Over-excitation protection
- total encapsulation

### DC ELECTRICAL SYSTEM:

- Battery trays
- Battery cables
- Battery hold down straps
- 3-stage battery charger with float, absorption, & bulk automatic charge stages

### WEATHER / SOUNDPROOF ALUMINUM HOUSING:

Corrosion Resistant Protection consisting of:

- (9) Heated and Agitated Wash Stages
- Zinc Phosphate Etching-Coating Stage
- Final Baked on Enamel Powder Coat
- 18/8 Stainless Steel Hardware

Design & specifications subject to change without prior notice. Dimensions shown are approximate. Contact Gillette for certified drawings. DO NOT USE DIMENSIONS FOR INSTALLATION PURPOSES.

