# **GILLETTE GENERATORS**

### LIQUID COOLED NAT. GAS ENGINE GENERATOR SET

Model		STANDBY 120°C RISE		
	HZ	LPG	N.G.	
<b>SP-2650-60 HERTZ</b>	60	170	265	



All generator sets are USA prototype built and thoroughly tested. Production models are USA factory built and 100% load tested.



UL2200, UL1446, UL508, UL142, UL498



NFPA 110, 99, 70, 37

All generator sets meet NFPA-110 Level 1, when equipped with the necessary accessories and installed per NFPA standards.



NEC 700, 701, 702, 708



NEMA ICS10, MG1, ICS6, AB1

**ANSI** ANSI C62.41, 27, 59, 32, 480, 40Q, 81U, 360-05



ASCE 7-05 & 7-10 All generator sets meet 180 MPH rating.

**EPA** EPA 40CFR Part 60, 1048, 1054, 1065, 1068



60 HZ MODEL

**SP-2650** 

"OPEN" GEN-SET

There is no enclosure, so gen-set must be placed within a weather protected area, un-inhabited by humans or animals, with proper ventilation. Silencer not supplied, as installation requirements are not known. However, this item is available as optional equipment.



"LEVEL 2" HOUSED GEN-SET Full aluminum weather protection and superior sound attenuation for specific low noise applications. <u>Critical grade muffler is standard</u>

GENER	ATOR	RATING	<u>GS</u>		LIQUID PROPAN	IE GAS FUEL	NATURAL GAS FUEL	
GENERATOR MODEL	VOL	TAGE	РН	HZ	120°C RISE STANDBY RATING		120°C RISE STANDBY RATING	
	L-N	L-L		••=	KW/KVA	AMP	KW/KVA	AMP
SP-2650-3-2	120	208	3	60	170/212	590	265/331	921
SP-2650-3-3	120	240	3	60	170/212	512	265/331	798
SP-2650-3-4	277	480	3	60	170/212	256	265/331	399
SP-2650-3-5	127	220	3	60	170/212	558	265/331	870
SP-2650-3-16	346	600	3	60	170/212	205	265/331	319

RATINGS: All three phase gen-sets are 12 lead windings, rated at .8 power factor. 120°C "STANDBY RATINGS" are strictly for gen-sets that are used for back-up emergency power to a failed normal utility power source. This standby rating allows varying loads, with no overload capability, for the entire duration of utility power outage. All gen-set power ratings are based on temperature rise measured by resistance method as defined by MIL-STD 705C and IEEE STD 115, METHOD 6.4.4. All generators have class H (180°C) insulation system on both rotor and stator windings. All factory tests and KW/KVA charts shown above are based on 120°C (standby) R/R winding temperature, within a maximum 40°C ambient condition. Generators operated at standby power ratings must not exceed the temperature rise limitation for class H insulation system, as specified in NEMA MG1-22.40. Specifications & ratings are subject to change without prior notice.

### **APPLICATION AND ENGINEERING DATA FOR MODEL SP-2650-60 HZ**

### **GENERATOR SPECIFICATIONS**

Manufacturer Stamford Electric Generators
Model & Type S4L1DD-311, 4 Pole, 12 Lead, Three Phase
HCI434D-17, 4 Pole, 4 Lead, 600V, Three Phase
Exciter Brushless, shunt excited
Voltage Regulator Solid State, HZ/Volts
Voltage Regulation <sup>1</sup> /2%, No load to full load
Frequency Field convertible, 60 HZ to 50 HZ
Frequency Regulation
Unbalanced Load Capability 100% of standby amps
Fotal Stator and Load InsulationClass H, 180°C
Γemperature Rise120°C R/R, standby rating @ 40°C amb.
3 Ø Motor Starting @ 30% Voltage Dip (208-240V) 500 kVA
3 Ø Motor Starting @ 30% Voltage Dip (480V)
3 Ø Motor Starting @ 30% Voltage Dip (600V)
Bearing1, Pre-lubed and sealed
Coupling Direct flexible disc
Fotal Harmonic Distortion    Max 3 % (MIL-STD705B)
Felephone Interference Factor         Max 50 (NEMA MG1-22)
Deviation FactorMax 5% (MIL-STD 405B)
Ltd. Warranty Period 24 Months from date of start-up or

### **GENERATOR FEATURES**

- World Renown Stamford Electric Generator having UL-1446 certification on full amortisseur windings.
- Full generator protection with **Deep Sea 7420** controller, having UL-508 certification.
- Automatic voltage regulator with over-excitation, underfrequency compensation, under-speed protection, and EMI filtering. Entire solid-state board is encapsulated for moisture protection.
- Generator power ratings are based on temperature rise, measured by resistance method, as defined in MIL-STD 705C and IEEE STD 115, Method 6.4.4.
- Power ratings will not exceed temperature rise limitation for class H insulation as per NEMA MG1-22.40.
- Insulation resistance to ground, exceeds 1.5 meg-ohm.
- Stator receives 2000 V. hi-potential test on main windings, and rotor windings receive a 1500 V. hi-potential test, as per MIL-STD 705B.
- Complete engine-generator torsional acceptance, confirmed during initial prototype testing.
- Full load testing on all engine-generator sets, before shipping.
- Self ventilating and drip-proof & revolving field design

### **ENGINE SPECIFICATIONS AND APPLICATIONS DATA**

### ENGINE

ManufacturerPower Solu	tions Inc. (PSI)
Model and Type Heavy Duty, 14.6L	TCAC, 4 cycle
Aspiration Turbocharged & Cha	rge Air Cooled
Cylinder Arrangement	Cylinders, Vee
Displacement Cu. In. (Liters)	892 (14.6)
Bore & Stroke In. (Cm.) 5.04 x 5.5	9 (12.8 x 14.2)
Compression Ratio	
Main Bearings & Style 10, Preci	sion Half-Shell
Cylinder Head	Cast Iron
Pistons	Cast Aluminum
Crankshaft	Forged Steel
Exhaust Valve	Inconel, A193
Governor	Electronic
Frequency Reg. (no load-full load)	Isochronous
Frequency Reg. (steady state)	± 1/4%
Air CleanerDry, Replace	eable Cartridge
Engine Speed	
Piston Speed, ft/min (m./min)	
Max Power, bhp (kwm) Standby/LPG	
Max Power, bhp (kwm) Standby/NG	402 (300)
Ltd. Warranty Period 12 Months or 2000 hrs	s., first to occur

### FUEL SYSTEM

Type LPG or NA	AT. GAS, Vapor Withdrawal
Fuel Pressure (kpa), in. H <sub>2</sub> O*	
Secondary Fuel Regulator	NG or LPG Vapor System
Auto Fuel Lock-Off Solenoid	Standard on all sets
Fuel Supply Inlet Line	

### FUEL CONSUMPTION

LP GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR)	STANDBY		
100% LOAD	926 (26.2)		
75% LOAD	789 (22.4)		
50% LOAD	532 (15.1)		
LPG = 2500 BTU X FT <sup>3</sup> /HR = Total BTU/HR LPG Conversion: 8.50 FT <sup>3</sup> = 1 LB. : 36.4 FT <sup>3</sup> = 1 GAL.			
NAT. GAS: FT <sup>3</sup> /HR (M <sup>3</sup> /HR) STANDBY			
100% LOAD	2782 (78.7)		
75% LOAD	2168 (61.4)		
50% LOAD	1522 (43.1)		
NG = 1000 BTU X FT <sup>3</sup> /HR = Total BTU/HR			

#### **OIL SYSTEM**

Type	Full Pressure
Oil Pan Capacity qt. (L)	
Oil Pan Cap. W/ filter qt. (L)	
Oil Filter	2, Replaceable Spin-On

### ELECTRICAL SYSTEM

Ignition System ...... Electronic Eng. Alternator/Starter: 24 VDC, negative ground, 45 amp/hr.

Recommended battery to  $-18^{\circ}C(0^{\circ} \text{ F})$ : ...(2) 12 VDC, BCI# 31, Max. Dimensions: 14"lg x 6 3/4" wi x 10" hi, with standard round posts. Min output 1000 CCA. Battery tray (max. dim. at 15"lg x 7"wi). This model has (2) battery trays, (2) hold down straps, (2) sets of battery cables, and (1) battery charger. Installation of (2) 12VDC starting batteries connected in series for 24VDC output is required, with possible higher AMP/HR rating, as described above, if the normal environment temperature averages  $-13^{\circ}$  F (-25°C) or cooler.

### **APPLICATION AND ENGINEERING DATA FOR MODEL SP-2650-60 HZ**

### **COOLING SYSTEM**

Type of System	Pressurized, closed recovery
Coolant Pump	Pre-lubricated, self-sealing
Cooling Fan Type (no. of blades)	Pusher (12)
Fan Diameter inches (mm)	
Ambient Capacity of Radiator °F (°C	C) 125 (51.6)
Engine Jacket Coolant Capacity Gal	(L) 9.5 (43.2)
Radiator Coolant Capacity Gal. (L).	
Maximum Restriction of Cooling Ai	r Intake
and discharge side of radiator in. $H_2$	0 (kpa) 0.5 (.125)
Water Pump Capacity gpm (L/min)	
Heat Reject Coolant: Btu/min (kw).	
Low Radiator Coolant Level Shutdo	wnStandard
Note: Coolant temp. shut-down switch setting (water/antifreeze) mix.	g at 230°F (110°C) with 50/50

### AIR REQUIREMENTS

Combustion Air, cfm (kg/hr)	532 (1064)
Radiator Air Flow cfm (m <sup>3</sup> /min)	
Heat Rejected to Ambient:	
Engine: kw (btu/min)	66.0 (3765)
Alternator: kw (btu/min)	

### EXHAUST SYSTEM

Exhaust Outlet Size	(2) 4'
Max. Back Pressure, in. hg (KPA).	3.0 (10.2)
Exhaust Flow, at rated kw: cfm (m <sup>3</sup> /min)	2521 (71.3)
Exhaust Temp., at rated kw: °F (°C)	
Engines are EPA certified for Natural Gas.	· · · · · · · · · · · · · · · · · · ·

### SOUND LEVELS MEASURED IN dB(A)

	Open	Level 2
	Set	Encl.
Level 2, Critical Silencer		80
Level 3, Hospital Silencer		75

Note: Open sets (no enclosure) has (2) optional silencer system choices due to unknown job-site applications. Level 2 enclosure has installed critical silencer with upgrade to hospital silencer. Sound tests are averaged from several test points and taken at 23 ft. (7 m) from source of noise at normal operation.

### **DERATE GENERATOR FOR ALTITUDE**

3% per 1000 ft. (305m) above 3000 ft. (914m) from sea level

### DERATE GENERATOR FOR TEMPERATURE

2% per 10°F (5.6°C) above 104F (40°C)

### **DIMENSIONS AND WEIGHTS**

	Open	Level 2	
	Ŝet	Enclosure	
Length in (cm)			
Width in (cm)			
Height in (cm)			
3 Ø Net Weight lbs (kg)		10675 (4842)	
3 Ø Net Weight lbs (kg)		11025 (5001)	

### DEEP SEA 7420 DIGITAL MICROPROCESSOR CONTROLLER



#### **Deep Sea 7420**

The "**7420**" controller is an auto start mains (utility) failure module for single gen-set applications. This controller includes a backlit LCD display which <u>continuously</u> displays the status of the engine and generator at all times.

The "**7420**" controller will also monitor speed, frequency, voltage, current, oil pressure, coolant temp., and fuel levels. These modules have been designed to display warning and shut down status. It also includes: (11) configurable inputs  $\bullet$  (8) configurable outputs  $\bullet$  voltage monitoring  $\bullet$  mains (utility) failure detection

• (250) event logs • configurable timers • automatic shutdown or warning during fault detection • remote start (on load) • engine preheat • advanced metering capability • hour meter • text LCD displays • protected solid state outputs • test buttons for: stop/reset • manual mode • auto mode • lamp test • start button • power monitoring (kWh, kVAr, kVAh, kVArh) This controller includes expansion features including RS232, RS484 (using MODBUS-RTU/TCP), direct USB connection with PC, expansion optioned using DSENet for remote annunciation and remote relay interfacing for a distance of up to 3300FT. The controller software is freely downloadable from the internet and allows monitoring with direct USB cable, LAN, or by internet via the built in web interface.

LOW LOAD CONDITIONS: Operation of PSI HD engines at low-load conditions should be limited to no more than one (1) hour per twenty-four (24) hour period. If the application requires extended time at light loads, it is recommended that the engine load be increased to at least 70% of mechanical rating for a minimum of two (2) hours per fifty (50) hours of low-load operation. Piston sealing rings rely on adequate cylinder firing pressure and temperature to seal the combustion chamber and prevent excessive engine oil from entering the power cylinder. Under low loads these rings will not seal properly, resulting in oil being burned in the combustion chamber and carbon deposits on pistons and valves. This mechanism is well-documented in reciprocating engines of all fuel types and is often referred to as "wet-stacking."

### **STANDARD FEATURES FOR MODEL SP-2650-60 HZ**

### **STANDARD FEATURES**

#### **CONTROL PANEL:**

Deep Sea 7420 digital microprocessor with

- logic allows programming in the field. Controller has:STOP-MANUAL-AUTO modes and automatic engine
- shutdowns, signaled by full text LCD indicators:
  Low oil pressure
  Engine fail to start
- Low oil pressureHigh engine temp
- Engine over speed
- Engine over speed
  Engine under speed
- Low Radiator Level
  Three auxiliary alarms
  Engine
  Over &
  - Over & under voltage
- Battery fail alarm

Also included is tamper-proof engine hour meter

#### **ENGINE:**

Full flow oil filter • Air filter • Oil pump • Solenoid type starter motor • Hi-temp radiator • Jacket water pump

• Thermostat • Pusher fan and guard • Exhaust manifold

• 24 VDC battery charging alternator • Flexible exhaust connector • "Isochronous" duty, electronic governor • Secondary dry fuel regulator • Dry fuel lock-off solenoid • Vibration isolators • Closed coolant recovery system with 50/50 water to anti-freeze mixture • flexible oil & radiator drain hose.

Design & specifications subject to change without prior notice. Dimensions shown are approximate. Contact Gillette for certified drawings. DO NOT USE DIMENSIONS FOR INSTALLATION PURPOSES.

#### AC GENERATOR SYSTEM:

AC generator • Shunt excited • Brushless design • Circuit Breaker installed and wired to gen-set • Direct connection to engine with flex disc • Class H, 180°C insulation • Self ventilated • Drip proof construction • UL Certified

#### **VOLTAGE REGULATOR:**

<sup>1</sup>/<sub>2</sub>% Voltage regulation • EMI filter • Under-speed protection • Over-excitation protection • total encapsulation

#### **DC ELECTRICAL SYSTEM:**

Battery tray • Battery cables • Battery hold down straps

• 2-stage battery float charger with maintaining & recharging automatic charge stages

## WEATHER/SOUND PROOF ALUMINUM HOUSING CORROSION RESISTANT PROTECTION CONSISTING OF:

- 9 Heated and Agitated Wash Stages
- Zinc Phosphate Etching-coating Stage
- Final Baked On Enamel Powder Coat
- 18/8 Stainless Steel Hardware





# **14.6L ENGINE**

# **INDUSTRIAL STATIONARY**

# **Product Overview**

The PSI HD 14.6L is a U.S. EPA-certified natural gas and propane engine developed from the block up to be a reliable and durable power unit. Built upon a proven marine-diesel grade block, the 6-cylinder in-line, turbocharged and aftercooled engine features replaceable wet liners and water-cooled exhaust.

Superior engine performance is provided by an ECU that integrates and coordinates all critical functions including: Governor, Variable Ignition Timing, Air Fuel Ratio Control, Knock Suppression and Engine Protection.

The PSI HD product lineup has six models with displacements of 8.1L, 11.1L, 14.6L, 18.3L and 21.9L. These engines are an extension of the PSI product line, which is based upon blocks from 650cc to 8.8L. All PSI engines feature the same fuel systems and controls, simplifying your application development and support.

### FEATURES

- U.S. EPA-Certified and CARB-Compliant
- Dual Fuel with Automatic Change-Over
- 50C Ambient Cooling Capacity
- 3-Way Catalytic Converter
- Air Filtration
- UL2200-Compliant or Listed Components
- MasterTrak Telematics service (included for 1 year)





# **14.6L ENGINE** Engineering Data

# **14.6L Industrial Stationary Engine**

Displacement	892 cid	14,620 cc			
Compression Ratio	10.5:	1			
Bore & Stroke	5.04 in x 5.59 in	128 mm x 142 mm			
kWe	300@1,800 rpm (Natural Gas)	225@1,500 rpm (Natural Gas)			
Emission-Certified	EPA, CARB – Industrial Stationary				
Fuel Types	Natural Gas / Propane				

### **GENERAL DATA**

- Water-cooled, turbo-charged, air-to-air inter-cooled, stoichiometric, replaceable wet cylinder liners
- Cast iron block & heads, 10.5:1 compression ratio, overhead valve/2V configuration
- Crankshaft gear-driven oil system with cartridge-type filter, belt-driven centrifugal water pump
- Full ECU engine control including: coil-on-plug variable timing ignition, electronic governor and fuel-air ratio control
- Engine protection for oil pressure, coolant level, coolant temperature, fuel pressure, over-speed
- Complete fuel system for single fuel (NG/LP) operation with closed-loop control
- Alternator (45A/24VDC)
- Starter (24VDC)
- CANBUS J1939 interface



Information may vary with application. All specifications listed are based on the latest product information available at the time of publication. The right is reserved to make changes at any time without notice. 201 Mittel Drive, Wood Dale, IL 60191 T: 630-350-9400 F: 630-350-9900 www.psiengines.com







### S4L1D-D41 Wdg.311 - Technical Data Sheet

#### Standards

Stamford industrial alternators meet the requirements of the relevant parts of the BS EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2-100 and As1359. Other standards and certifications can be considered on request.

#### **Quality Assurance**

Alternators are manufactured using production procedures having a quality assurance level to BS EN ISO 9001.



#### **Excitation and Voltage Regulators**

Excitation System									
AVR Type	AS440	MX341	MX321						
Voltage Regulation	± 1%	± 1%	± 0.5%		with 4% Engine Governing				
Excitation Type	Self-Excited	PMG	PMG						

No Load Excitation Voltage (V)	12 - 9
No Load Excitation Current (A)	0.7 - 0.5
Full Load Excitation Voltage (V)	41 - 39
Full Load Excitation Current (A)	2.3 - 2.2
Exciter Time Constant (seconds)	0.105



Electrical Data									
Insulation System				С	lass H				
Stator Winding				Double	e Layer Lap				
Winding Pitch				Tw	o Thirds				
Winding Leads									
Winding Number					311				
Number of Poles					4				
IP Rating					IP23				
RFI Suppression		BS EN (	61000-6-2	& BS EN 61 Refer to fa	000-6-4,VD	E 0875G, VI ers	DE 0875N.		
Waveform Distortion	N	O LOAD <	1.5% NON	I-DISTORT	ING BALAN		R LOAD < 5.	0%	
Short Circuit Ratio					1/Xd				
Steady State X/R Ratio					12.29				
		50 Hz 60 Hz							
Telephone Interference		THF	<2%			TIF	-<50		
Cooling Air		0.83 m	1 <sup>3</sup> /sec			0.99	m³/sec		
Voltage Star	380	400	415	440	416	440	460	480	
kVA Base Rating (Class H) for Reactance Values	300	310	310	290	344	370	375	390	
Saturated Values in Per Ur	nit at Bas	e Rating	is and V	oltages				·	
Xd Dir. Axis Synchronous	3.15	2.94	2.73	2.27	3.60	3.46	3.21	3.07	
X'd Dir. Axis Transient	0.20	0.19	0.17	0.14	0.22	0.21	0.20	0.19	
X"d Dir. Axis Subtransient	0.14	0.13	0.12	0.10	0.15	0.14	0.13	0.12	
Xq Quad. Axis Reactance	2.66	2.48	2.30	1.92	3.09	2.97	2.75	2.63	
X"q Quad. Axis Subtransient	0.40	0.37	0.34	0.29	0.40	0.39	0.36	0.34	
XL Stator Leakage Reactance	0.07	0.06	0.06	0.05	0.09	0.08	0.08	0.07	
X2 Negative Sequence Reactance	0.27	0.25	0.23	0.19	0.28	0.27	0.25	0.24	
X0 Zero Sequence Reactance	0.10	0.09	0.09	0.07	0.10	0.09	0.09	0.08	
Unsaturated Values in Per	Unit at E	Base Rat	ings and	l Voltage	s				
Xd Dir. Axis Synchronous	3.78	3.53	3.28	2.73	4.32	4.16	3.85	3.68	
X'd Dir. Axis Transient	0.23	0.21	0.20	0.17	0.25	0.24	0.23	0.22	
X"d Dir. Axis Subtransient	0.17	0.16	0.15	0.12	0.17	0.16	0.15	0.15	
Xq Quad. Axis Reactance	2.74	2.55	2.37	1.97	3.18	3.06	2.84	2.71	
X"q Quad. Axis Subtransient	0.48	0.48 0.45 0.41 0.34 0.48 0.46 0.43 (							
XL Stator Leakage Reactance	0.08	0.07	0.07	0.05	0.10	0.09	0.09	0.08	
XIr Rotor Leakage Reactance	0.12	0.11	0.10	0.09	0.14	0.13	0.12	0.12	
X2 Negative Sequence Reactance	0.32	0.30	0.28	0.23	0.34	0.32	0.30	0.29	
X0 Zero Sequence Reactance	0.12	0.11	0.10	0.08	0.11	0.11	0.10	0.10	



Time Constants (Seconds)							
T'd TRANSIENT TIME CONST.	(	0.08					
T"d SUB-TRANSTIME CONST.	0	.019					
T'do O.C. FIELD TIME CONST.		1.7					
Ta ARMATURE TIME CONST.	0.018						
T"q SUB-TRANSTIME CONST.	0.	0077					
Resistances in Ohms ( $\Omega$ ) at 22 <sup>0</sup>							
Stator Winding Resistance (Ra), per phase for series connected	0.	0124					
Rotor Winding Resistance (Rf)	1	05					
Exciter Stator Winding Resistance		18					
Exciter Rotor Winding Resistance per							
phase	0	.068					
PMG Phase Resistance (Rpmg) per phase		1.9					
Positive Sequence Resistance (R1)	0.	0155					
Negative Sequence Resistance (R2)	0.017856						
Zero Sequence Resistance (R0)	0.0155						
Saturation Factors	400V	480V					
SG1.0	0.31	0.31					
SG1.2	1.25	1.25					
Mechanical Data							
Shaft and Keys	All alternator rotors are dynamically balance minimum vibration in operation. Two beau	ed to better than BS6861: Part 1 Grade 2.5 for ring generators are balanced with a half key.					
	1 Bearing	2 Bearings					
SAE Adaptor	SAE 0.5, 1	N/A					
Moment of Inertia	4.0771 kgm2	N/A					
Weight Wound Stator	415 kg	N/A					
Weight Wound Rotor	361 kg	N/A					
Weight Complete Alternator	940 kg	N/A					
Shipping weight in a Crate	1010 kg	N/A					
Packing Crate Size	155 x 87 x 107(cm) N/A						
Maximum Over Speed	2250 RPM for two minutes						
Bearing Drive End	N/A	N/A					
Bearing Non-Drive End	Ball 6314	N/A					



### THREE PHASE EFFICIENCY CURVES







Transient Voltage	Dip Scaling Factor	Transient Voltage Rise Scaling Factor
PF	Factor	
< 0.5	1	For voltage rise multiply voltage dip by 1.25
0.5	0.97	
0.6	0.93	
0.7	0.9	
0.8	0.85	
0.9	0.83	]







Transient Voltage	Dip Scaling Factor	Transient Voltage Rise Scaling Factor
PF	Factor	
< 0.5	1	For voltage rise multiply voltage dip by 1.25
0.5	0.97	
0.6	0.93	
0.7	0.9	
0.8	0.85	
0.9	0.83	

### STAMFORD S4L1D-D41 Wdg.311

#### **Three-phase Short Circuit Decrement Curve**





#### Sustained Short Circuit = 1300 Amps

#### Note 1

The following multiplication factors should be used to adjust the values from curve between time 0.001 seconds and the minimum current point in respect of nominal operating voltage :

50Hz		60Hz	
Voltage	Factor	Voltage	Factor
380V	X 1.00	416V	X 1.00
400V	X 1.05	440V	X 1.06
415V	X 1.09	460V	X 1.10
440V	X 1.16	480V	X 1.15

The sustained current value is constant irrespective of voltage level

#### Note 2

The following multiplication factor should be used to convert the values calculated in accordance with NOTE 1 to those applicable to the various types of short circuit :

	3-phase	2-phase L-L	1-phase L-N
Instantaneous	x 1.00	x 0.87	x 1.30
Minimum	x 1.00	x 1.80	x 3.20
Sustained	x 1.00	x 1.50	x 2.50
Max. sustained duration	10 sec.	5 sec.	2 sec.

All other times are unchanged

#### Note 3

Curves are drawn for Star connected machines under no-load excitation at rated speeds. For other connection the following multipliers should be applied to current values as shown : Parallel Star = Curve current value X 2 Series Delta = Curve current value X 1.732

## **STAMFORD**

### S4L1D-D41 Wdg.311

### **Typical Alternator Operating Charts**







#### **RATINGS AT 0.8 POWER FACTOR**

	Class - Temp Rise	St	andby -	163/27	°C	St	andby -	- 150/40	°℃	С	ont. H -	125/40	°C	C	ont. F -	105/40	°C
50	Series Star (V)	380	400	415	440	380	400	415	440	380	400	415	440	380	400	415	440
50	kVA	330	340	340	320	320	330	330	310	300	310	310	290	280	285	285	270
HZ	kW	264	272	272	256	256	264	264	248	240	248	248	232	224	228	228	216
	Efficiency (%)	92.1	92.3	92.6	93.2	92.3	92.5	92.7	93.3	92.7	92.9	93.1	93.6	93.1	93.3	93.4	93.8
	kW Input	287	295	294	275	277	285	285	266	259	267	266	248	241	244	244	230
60	Series Star (V)	416	440	460	480	416	440	460	480	416	440	460	480	416	440	460	480
	kVA	375	410	415	430	365	400	400	415	344	370	375	390	315	340	345	355
112	kW	300	328	332	344	292	320	320	332	275	296	300	312	252	272	276	284
	Efficiency (%)	92.4	92.2	92.5	92.6	92.5	92.4	92.7	92.8	92.8	92.9	93.1	93.1	93.2	93.2	93.4	93.5
	kW Input	325	356	359	372	316	346	345	358	296	319	322	335	270	292	295	304

#### De-Rates

All values tabulated above are subject to the following reductions:

- 5% when air inlet filters are fitted
- 3% for every 500 meters by which the operating altitude exceeds 1000 meters above mean sea level
- 3% for every 5 °C by which the operational ambient temperature exceeds 40 °C
- For any other operating conditions impacting the cooling circuit please refer to applications

Note: Requirement for operating in an ambient exceeding 60 °C and altitude exceeding 4000 meters must be referred to applications.

#### Dimensional and Torsional Drawing

For dimensional and torsional information please refer to the alternator General Arrangement and rotor drawings available on our website (http://stamford-avk.com/)

**Note:** Continuous development of our products means that the information contained in our data sheets can change without notice, and specifications should always be confirmed with Cummins Generator Technologies prior to purchase.







View our videos at youtube.com/stamfordavk

news.stamford-avk.com

For Applications Support: applications@cummins.com

For Customer Service: service-engineers@stamford-avk.com

For General Enquiries: info@cumminsgeneratortechnologies.com

Copyright 2016. Cummins Generator Technologies Ltd. All rights reserved. Cummins and the Cummins logo are registered trade marks of Cummins Inc. STAMFORD is a registered trade mark of Cummins Generator Technologies Ltd.





### HCI434D/444D - Winding 17

Technical Data Sheet



HCI434D/444D



#### **SPECIFICATIONS & OPTIONS**

#### **STANDARDS**

Stamford industrial generators meet the requirements of BS EN 60034 and the relevant section of other international standards such as BS5000, VDE 0530, NEMA MG1-32, IEC34, CSA C22.2-100, AS1359.

Other standards and certifications can be considered on request.

#### **VOLTAGE REGULATORS**

#### AS440 AVR - STANDARD

With this self-excited system the main stator provides power via the Automatic Voltage Regulator (AVR) to the exciter stator. The high efficiency semi-conductors of the AVR ensure positive build-up from initial low levels of residual voltage.

The exciter rotor output is fed to the main rotor through a three-phase full-wave bridge rectifier. The rectifier is protected by a surge suppressor against surges caused, for example, by short circuit or out-of-phase paralleling. The AS440 will support a range of electronic accessories.

including a 'droop' Current Transformer (CT) to permitparallel operation with other ac generators.

#### MX341 AVR

This sophisticated AVR is incorporated into the Stamford Permanent Magnet Generator (PMG) control system.

The PMG provides power via the AVR to the main exciter, giving a source of constant excitation power independent of generator output. The main exciter output is then fed to the main rotor, through a full wave bridge, protected by a surge suppressor. The AVR has in-built protection against sustained over-excitation, caused by internal or external faults. This de-excites the machine after a minimum of 5 seconds.

An engine relief load acceptance feature can enable full load to be applied to the generator in a single step.

If three-phase sensing is required with the PMG system the MX321 AVR must be used.

We recommend three-phase sensing for applications with greatly unbalanced or highly non-linear loads.

#### MX321 AVR

The most sophisticated of all our AVRs combines all the features of the MX341 with, additionally, three-phase rms sensing, for improved regulation and performance. Over voltage protection is built-in and short circuit current level adjustments is an optional facility.

#### WINDINGS & ELECTRICAL PERFORMANCE

All generator stators are wound to 2/3 pitch. This eliminates triplen (3rd, 9th, 15th ...) harmonics on the voltage waveform and is found to be the optimum design for trouble-free supply of non-linear loads. The 2/3 pitch design avoids excessive neutral currents sometimes seen with higher winding pitches, when in parallel with the mains. A fully connected damper winding reduces oscillations during paralleling. This winding, with the 2/3 pitch and carefully selected pole and tooth designs, ensures very low waveform distortion.

#### **TERMINALS & TERMINAL BOX**

Standard generators are 3-phase reconnectable with 12 ends brought out to the terminals, which are mounted on a cover at the non-drive end of the generator. A sheet steel terminal box contains the AVR and provides ample space for the customers' wiring and gland arrangements. It has removable panels for easy access.

#### SHAFT & KEYS

All generator rotors are dynamically balanced to better than BS6861:Part 1 Grade 2.5 for minimum vibration in operation. Two bearing generators are balanced with a half key.

#### INSULATION/IMPREGNATION

The insulation system is class 'H'.

All wound components are impregnated with materials and processes designed specifically to provide the high build required for static windings and the high mechanical strength required for rotating components.

#### QUALITY ASSURANCE

Generators are manufactured using production procedures having a quality assurance level to BS EN ISO 9001.

The stated voltage regulation may not be maintained in the presence of certain radio transmitted signals. Any change in performance will fall within the limits of Criteria 'B' of EN 61000-6-2:2001. At no time will the steady-state voltage regulation exceed 2%.

#### DE RATES

All values tabulated on page 6 are subject to the following reductions

5% when air inlet filters are fitted.

3% for every 500 metres by which the operating altitude exceeds 1000 metres above mean sea level.

3% for every 5 C by which the operational ambient temperature exceeds 40 C.

Note: Requirement for operating in an ambient exceeding 60 C must be referred to the factory.

NB Continuous development of our products entitles us to change specification details without notice, therefore they must not be regarded as binding.

Front cover drawing typical of product range.

### STAMFORD

### HCI434D/444D

### WINDING 17

CONTROL SYSTEM	SEPARATELY EXCITED BY P.M.G.						
A.V.R.	MX321 MX341	MX321 MX341					
VOLTAGE REGULATION	± 0.5 % ± 1.0 % With 4% ENGINE GOVERNING						
SUSTAINED SHORT CIRCUIT	REFER TO SHORT CIRCU	REFER TO SHORT CIRCUIT DECREMENT CURVES (page 5)					
			- ((- <b>0</b> )				
CONTROL SYSTEM	SELF EXCITED						
A.V.R.	AS440						
VOLTAGE REGULATION	± 1.0 % With 4% ENGI	NE GOVERNING					
SUSTAINED SHORT CIRCUIT	WILL NOT SUSTAIN A SHO	ORT CIRCUIT					
INSULATION SYSTEM		CLAS	IS H				
PROTECTION		IP2	3				
RATED POWER FACTOR		0.8	3				
STATOR WINDING		DOUBLE LA	AYER LAP				
	5	TWOT	HRDS				
WINDING LEADS							
STATOR WDG. RESISTANCE	0.02 Ohr	<b>ns P</b> ER PHASE AT 22°C	SERIES STAR CONNECTED				
ROTOR WDG. RESISTANCE	-	1.05 Ohms	at 22°C				
EXCITER STATOR RESISTANCE	18 Ohms at 22°C						
EXCITER ROTOR RESISTANCE	0.068 Ohms PER PHASE AT 22°C						
R.F.I. SUPPRESSION	BS EN 61000-6-2 & BS EN 61000-6-4, VDE 0875G, VDE 0875N. refer to factory for others						
WAVEFORM DISTORTION	NO LOAD < 1.5% NON-DISTORTING BALANCED LINEAR LOAD < 5.0%						
MAXIMUM OVERSPEED	2250 Rev/Min						
	BALL 6317 (ISO)						
BEARING NON-DRIVE END	BALL. 6314 (ISO)						
	I BEAR		2 BEARING				
WEIGHT WOUND STATOR	940 R 415 R	9	950 kg 415 kg				
	361	9 0	338 kg				
	4 0771	g am <sup>2</sup>	3 8783 kgm <sup>2</sup>				
SHIPPING WEIGHTS in a crate	1010	Ka	1010 kg				
PACKING CRATE SIZE	155 x 87 x 1	107(cm)	155 x 87 x 107(cm)				
TELEPHONE INTERFERENCE	THF	2%	TIF<50				
COOLING AIR	6	0.99 m³/sec	2100 cfm				
VOLTAGE SERIES STAR	-	600	V				
VOLTAGE PARALLEL STAR		300	V				
VOLTAGE SERIES DELTA		346	SV				
kVA BASE RATING FOR REACTANCE		37	5				
		2.9	6				
		0.1	8				
X"d DIR AXIS SUBTRANSIENT	0.10						
	2 54						
X"a QUAD AXIS SUBTRANSIENT	0.34						
	0.54						
X2 NEGATIVE SEQUENCE	0.07						
	0.22						
REACTANCES ARE SATURAT	L VALUES ARE PER UNIT AT RATING AND VOI TAGE INDICATED						
T'd TRANSIENT TIME CONST.	0.08s						
T"d SUB-TRANSTIME CONST.		0.01	9s				
T'do O.C. FIELD TIME CONST.		1.7	s				
Ta ARMATURE TIME CONST.		0.01	8s				
SHORT CIRCUIT RATIO	1/Xd						



### HCI434D/444D

Winding 17



**STAMFORD** 

### HCI434D/444D

Winding 17

### THREE PHASE EFFICIENCY CURVES







Sustained Short Circuit = 1100 Amps

#### Note

The following multiplication factor should be used to convert the values from curve for the various types of short circuit :

	3-phase	2-phase L-L	1-phase L-N
Instantaneous	x 1.00	x 0.87	x 1.30
Minimum	x 1.00	x 1.80	x 3.20
Sustained	x 1.00	x 1.50	x 2.50
Max. sustained duration	10 sec.	5 sec.	2 sec.

All other times are unchanged

### HCI434D/444D



### Winding 17 / 0.8 Power Factor

### **60**Hz

### RATINGS







Head Office Address: Barnack Road, Stamford Lincolnshire, PE9 2NB United Kingdom Tel: +44 (0) 1780 484000 Fax: +44 (0) 1780 484100

www.cumminsgeneratortechnologies.com

Copyright 2010, Cummins Generator Technologies Ltd, All Rights Reserved Stamford and AvK are registered trade marks of Cummins Generator Technologies Ltd Cummins and the Cummins logo are registered trade marks of Cummins Inc.





## DSE**7410/20** AUTO START & AUTO MAINS FAILURE MODULES



The DSE7410 is an Auto Start Control Module and the DSE7420 is an Auto Mains (Utility) Failure Control Module suitable for a wide variety of single, diesel or gas, gen-set applications.

A sophisticated module monitoring an extensive number of engine parameters, the DSE74xx will annunciate warnings, shutdown and engine status information on the back-lit LCD screen, illuminated LED, remote PC, audible alarm and via SMS text alerts. The module includes RS232, RS485 & Ethernet ports as well as dedicated terminals for system expansion. The DSE7400 Series modules are compatible with electronic (CAN) and non-electronic (magnetic pickup/alternator sensing) engines and offer a comprehensive number of flexible inputs, outputs and extensive engine protections so the system can be easily adapted to meet the most demanding industry paralleling requirements.

The modules can be easily configured using the DSE Configuration Suite Software. Selected front panel editing is also available.

#### ENVIRONMENTAL TESTING STANDARDS

#### ELECTRO-MAGNETIC COMPATIBILITY

BS EN 61000-6-2 EMC Generic Immunity Standard for the Industrial Environment BS EN 61000-6-4 EMC Generic Emission Standard for the Industrial Environment

ELECTRICAL SAFETY BS EN 60950 Safety of Information Technology Equipment,

Safety of Information Technology Equipmer including Electrical Business Equipment

**TEMPERATURE** BS EN 60068-2-1 Ab/Ae Cold Test -30 °C BS EN 60068-2-2 Bb/Be Dry Heat +70 °C

#### VIBRATION

BS EN 60068-2-6 Ten sweeps in each of three major axes 5 Hz to 8 Hz @ +/-7.5 mm, 8 Hz to 500 Hz @ 2 gn

#### HUMIDITY

BS EN 60068-2-30 Db Damp Heat Cyclic 20/55 °C @ 95% RH 48 Hours BS EN 60068-2-78 Cab Damp Heat Static 40 °C @ 93% RH 48 Hours

#### SHOCK

BS EN 60068-2-27 Three shocks in each of three major axes 15 gn in 11 mS

#### DEGREES OF PROTECTION PROVIDED BY ENCLOSURES

BS EN 60529 IP65 - Front of module when installed into the control panel with the supplied sealing gasket.

ISSUE 1

## COMPREHENSIVE FEATURE LIST TO SUIT A WIDE VARIETY OF GEN-SET APPLICATIONS

( 🤅 🕑 🗛 🔝 🖉 🏰 🥵 🦛

DSE2130 DSE2131 DSE2133 DSE2152 DSE2152 DSE2548	MODEM MO 232 485			Ý.	<b>)</b> 11		× •		虍	4	đ		i i	
DSENET EXPANSION	RS232 AND RS485	US PC	SBU: DRTH	SB CONFIG OST INPUTS	URABLE	DC 0	OUTPUTS	AS	NALOGUI ENDERS	E	EMERGE STOP	NCY	DC POWER SUPPLY 8-35V	
		-		HERNET	`~ <b>↓</b>	t 	· · ·		-	<b>-</b> -	4	ř.		
DSE741	0/20 (€												DEUTZ ISUZU PERKINS CATERPILLAR MTU VOLVO CUMMINS SCANIA	
MAINS (UTILITY) SE BUS SENSING (DSE	NSING (DSE7420) 7410)	N/C VOL OUTPUT	LT FREE T	N/O VOLT FREE OUTPUT	GENERA	TOR SEI	NSING		CHARG ALTERN	E IATOR	FUEL & C OUTPUTS FLEXIBLE WI	RANK S ITH CAN	ELECTRONIC ENGINES & MAGNETIC PICK-U	JP
	S	џ′₊	, , ,	Į∕,		ENT J		rs )	D · W/	+ /L	µ′1 +			52
圍_	1ph 2ph 3ph N	~				1ph 2ph 3ph E N		1ph 2ph 3ph N						





## DSE7410/20 **AUTO START & AUTO MAINS FAILURE MODULES**

DSE7420

2

MARY MARKED



DSE7410



#### **KEY FEATURES**

- Configurable inputs (11)
- Configurable outputs (8)
- Voltage measurement
- Mains (utility) failure detection
- Dedicated load test button
- kW overload alarms
- Comprehensive electrical protection
- RS232, RS485 & Ethernet remote communications
- Modbus RTU/TCP •
- PLC functionality
- Multi event exercise timer •
- Back-lit LCD 4-line text display
- Multiple display languages •
- Automatic start/Manual start •
- Audible alarm
- Fixed and flexible LED indicators •
- Event log (250)
- Engine protection
- Fault condition notification to a designated PC
- Front panel mounting Protected front panel

**RELATED MATERIALS** 

DSE74xx Operator Manual

programming

TITLE

- Configurable alarms and timers •
- Configurable start and stop timers

DSE7410 Installation Instructions

SE7420 Installation Instructions DSE74xx Quick Start Guide

DSE74xx PC Configuration Suite Manual

#### · Five key menu navigation

- Front panel editing with PIN protection
- 3 configurable maintenance alarms
- CAN and magnetic pick-up/Alt. sensing
- Fuel usage monitor and low fuel alarms
- Charge alternator failure alarm
- Manual speed control (on
- compatible CAN engines) Manual fuel pump control
- "Protections disabled" feature
- Reverse power protection
- Power monitoring (kW h, kV Ar, kV A h, kV Ar h)
- Load switching (load shedding
- and dummy load outputs) Automatic load transfer (DSE7420)
- Unbalanced load protection
- Independent earth fault trip •
- Fully configurable via DSE
- Configuration Suite PC software
- Configurable display languages
- Remote SCADA monitoring via DSE Configuration Suite PC

software

- Advanced SMS messaging (additional external modem required)
- Start & stop capability via SMS messaging
- Additional display screens to help with modem diagnostics
- DSENet® expansion
- Integral PLC editor

#### **KEY BENEFITS**

T

- RS232, RS485 & Ethernet can be used at the same time
- DSENet<sup>®</sup> connection for
- system expansion
- PLC functionality
- Five step dummy load support
- Five step load shedding support
- High number of inputs and outputs
- Worldwide language support
- Direct USB connection to PC
- Ethernet monitoring
- USB host
- Data logging & trending
- 8 mm 0.3" STORAGE TEMPERATURE RANGE -40 °C to +85 °C

PART NO'S 053-085 053-088 057-162 057-161 057-160

DEEP SEA ELECTRONICS PLC UK

Highfield House, Hunmanby Industrial Estate, Hunmanby YO14 0PH **TELEPHONE** +44 (0) 1723 890099 **FACSIMILE** +44 (0) 1723 893303 EMAIL sales@deepseaplc.com WEBSITE www.deepseaplc.com

Deep Sea Electronics Plc maintains a policy of continuous development and reserves the right to change the details shown on this data sheet without prior notice. The contents are intended for guidance only.

#### DEEP SEA ELECTRONICS INC USA

3230 Williams Avenue, Rockford, IL 61101-2668 USA TELEPHONE +1 (815) 316 8706 FACSIMILE +1 (815) 316 8708 EMAIL sales@deepseausa.com WEBSITE www.deepseausa.com

### SPECIFICATION

CONTINUOUS VOLTAGE RATING 8 V to 35 V Continuous

#### CRANKING DROPOUTS

Able to survive 0 V for 50 mS, providing supply was at least 10 V before dropout and supply recovers to 5 V. This is achieved without the need for internal batteries

MAXIMUM OPERATING CURRENT 260 mA at 12 V. 130 mA at 24 V

MAXIMUM STANDBY CURRENT 120 mA at 12 V, 65 mA at 24 V

CHARGE FAIL/EXCITATION RANGE 0 V to 35 V

OUTPUTS OUTPUT A (FUEL) 15 A DC at supply voltage

OUTPUT B (START) 15 A DC at supply voltage

OUTPUTS C & D 8 A AC at 250 V AC (Volt free)

AUXILIARY OUTPUTS E,F,G,H,I & J 2 A DC at supply voltage

#### GENERATOR VOLTAGE RANGE 15 V to 333 V AC (L-N)

FREQUENCY RANGE 3.5 Hz to 75 Hz

MAINS (UTILITY) (DSE7420) **VOLTAGE RANGE** 15 V to 333 V AC (L-N)

#### FREQUENCY RANGE 3.5 Hz to 75 Hz

BUS (DSE7410) VOLTAGE RANGE 15 V to 333 V AC (L-N)

#### FREQUENCY RANGE 3.5 Hz to 75 Hz

MAGNETIC PICK UP VOLTAGE RANGE +/- 0.5 V to 70 V

#### FREQUENCY RANGE 10,000 Hz (max)

DIMENSIONS OVERALL 240 mm x 172 mm x 57 mm 9.4" x 6.8" x 2.2

PANEL CUTOUT 220 mm x 160 mm 8.7" x 6.3"

MAXIMUM PANEL THICKNESS

Part Number: PDG33G0400B2NJNNNNNN



PRODUCT VIEW (Use Mouse to Rotate and Zoom)

Eaton's Power Defense<sup>™</sup> molded case circuit breakers, a globally rated platform designed to help keep your power system safe with latest protection technology. Engineered for the future: IoT and Industry 4.0 features such as built-in communications, advanced energy metering, and algorithms that signal breaker maintenance; zone selective interlock technology that clears faults quickly and locally; ArcFlash reduction options that help protect your people, and not to mention Eaton's best-inclass support and service.

### **Tech Data for Configured Product**

Power Defense Catalog Number	PDG33G0400B2NJNNNNN
Frame Size	Frame 3
Poles	3 Pole
Voltage	480V AC
Interruption or Breaking Capacity ( Icu/Ics)	35kA
Continuous Current Rating (In)	400A
Trip Unit Type	PXR10
Trip Unit Options 1	LSI
Trip Unit Options 2	None
Indicating Accessories	None
Indicating Accessories Terminal	None
Tripping Accessories	None
Tripping Accessory Terminal	None
Tripping Accessory Voltage	None
Line Type Description	Option 1 - Standard Terminal
Line Conductor Options	(2) 3/0 - 250
Line Terminal Type	Aluminum
Load Type Description	Option 1 - Standard Terminal
Load Conductor Options	(2) 3/0 - 250
Load Terminal Type	Aluminum
Special Options - Type of Modification	None
Details	None
Additional Description	None

### Molded Case Circuit Breakers Power Defense ™ UL Global Series Part Number: PDG33G0400B2NJNNNNN



Datasheet creation date: 02/12/2019

### **Technical drawings**







### **General Technical Data**

Frame Rating (In)	400A			
Reference Standard	UL489, CSA 22.2, IEC 60947-2 & GB			
Number of poles	3			
Neutral rating	-			
Interruption Rating Designator	F/G/K/M/N/P			
UL Interruption Rating to UL 489 (240Vac)	35 / 65 / 85 / 100 / 150 / 200kA			
UL Interruption Rating to UL 489 (480Vac)	25 / 35 / 50 / 65(a) / 85 / 100kA			
UL Interruption Rating to UL 489 (600Vac)	14 / 18 / 25 / 35 / 50 / 65kA			
UL Interruption Rating to UL 489 (125/250Vdc)				
UL Current Limiting	N / N / N / Y / Y / Y			
Rated breaking capacity to IEC 60947-2 (220-240 Vac Icu)	35 / 55 / 85 / 100 / 150 / 200kA			
Rated breaking capacity to IEC 60947-2 (220-240 Vac Ics)	35 / 55 / 85 / 100 / 100 / 150kA			
Rated breaking capacity to IEC 60947-2 (380-415 Vac Icu)	25 / 36 / 50 / 70 / 70 / 100kA			
Rated breaking capacity to IEC 60947-2 (380-415 Vac Ics)	25 / 36 / 50 / 53 / 70 / 70kA			
Rated breaking capacity to IEC 60947-2 (440 Vac Icu)	25 / 30 / 35 / 50 / 70 / 100kA			
Rated breaking capacity to IEC 60947-2 (440 Vac Ics)	20 / 22.5 / 35 / 40 / 50 / 50kA			
Rated breaking capacity to IEC 60947-2 (525 Vac Icu)	18 / 20 / 25 / 30 / 35 / 40kA			
Rated breaking capacity to IEC 60947-2 (525 Vac Ics)	5 / 7.5 / 10 / 15 / 25 / 25kA			
Rated breaking capacity to IEC 60947-2 (690 Vac Icu)	- / 8 / 10 / 15 / 20 / 20kA			
Rated breaking capacity to IEC 60947-2 (690 Vac Ics)	- / 4 / 5 /7. 5 / 10 / 10kA			
Rated breaking capacity to IEC 60947-2 (125V DC Icu)				
Rated breaking capacity to IEC 60947-2 (250V DC 2P in series Ics)	10 / 10 / 10 / 22 / 22 / 22kA			
Frequency	50/60Hz			
Trip Unit Type	PXR10			
Continuous Current Range	160 - 400A			
100% UL489 Rated	Yes			
Instantaneous/Short Circuit Range	2 - 10 ln			
Magnetic/Instantaneous Override	4400A			
Dimensions H x W x D (inches)	10.125 x 5.47 x 4.297			
Pole to pole distance inches	1,719			
Approx Weight Ibs	16			
RoHS Compliance	Yes			
UL File Number	E7819			
Ambient Temp Calibration				
Derating at 50C				
Derating at 60C				
Derating at 70C				

1. 480Vac corresponds to 277Vac for 1P

2. 600Vac corresponds to 347Vac for 1P

Part Number: PDG43G0800B2NJNNNNNN



PRODUCT VIEW (Use Mouse to Rotate and Zoom)

Eaton's Power Defense<sup>™</sup> molded case circuit breakers, a globally rated platform designed to help keep your power system safe with latest protection technology. Engineered for the future: IoT and Industry 4.0 features such as built-in communications, advanced energy metering, and algorithms that signal breaker maintenance; zone selective interlock technology that clears faults quickly and locally; ArcFlash reduction options that help protect your people, and not to mention Eaton's best-inclass support and service.

### **Tech Data for Configured Product**

Power Defense Catalog Number	PDG43G0800B2NJNNNNN
Frame Size	Frame 4
Poles	3 Pole
Voltage	240V AC
Interruption or Breaking Capacity ( Icu/Ics)	55kA
Continuous Current Rating (In)	800A
Trip Unit Type	PXR10
Trip Unit Options 1	LSI
Trip Unit Options 2	None
Indicating Accessories	None
Indicating Accessories Terminal	None
Tripping Accessories	None
Tripping Accessory Terminal	None
Tripping Accessory Voltage	None
Line Type Description	Option 1 - Standard Terminal
Line Conductor Options	(3) 3/0 - 400
Line Terminal Type	Aluminum
Load Type Description	Option 1 - Standard Terminal
Load Conductor Options	(3) 3/0 - 400
Load Terminal Type	Aluminum
Special Options - Type of Modification	None
Details	None
Additional Description	None

### Molded Case Circuit Breakers Power Defense ™ UL Global Series Part Number: PDG43G0800B2NJNNNNN



### **Technical drawings**





### **General Technical Data**

Frame Rating (In)	800A
Reference Standard	UL489, CSA 22.2, IEC 60947-2 & GB
Number of poles	3
Neutral rating	-
Interruption Rating Designator	G/K/M
UL Interruption Rating to UL 489 (240Vac)	65 / 85 / 100kA
UL Interruption Rating to UL 489 (480Vac)	35 / 50 / 65(a)kA
UL Interruption Rating to UL 489 (600Vac)	18 / 25 / 35kA
UL Interruption Rating to UL 489 (125/250Vdc)	
UL Current Limiting	-
Rated breaking capacity to IEC 60947-2 (220-240 Vac Icu)	55 / 85 / 100 / 100kA
Rated breaking capacity to IEC 60947-2 (220-240 Vac Ics)	55 / 85 / 100 / 100kA
Rated breaking capacity to IEC 60947-2 (380-415 Vac Icu)	36 / 50 / 70 / 70kA
Rated breaking capacity to IEC 60947-2 (380-415 Vac Ics)	36 / 50 / 53 / 70kA
Rated breaking capacity to IEC 60947-2 (440 Vac Icu)	30 / 35 / 50 / 65kA
Rated breaking capacity to IEC 60947-2 (440 Vac Ics)	22.5 / 35 / 40 / 50kA
Rated breaking capacity to IEC 60947-2 (525 Vac Icu)	20 / 25 / 30 / 35kA
Rated breaking capacity to IEC 60947-2 (525 Vac Ics)	16.5 / 20 / 25 / 25kA
Rated breaking capacity to IEC 60947-2 (690 Vac Icu)	8 / 10 / 15 / 20kA
Rated breaking capacity to IEC 60947-2 (690 Vac Ics)	4 / 5 /7. 5 / 10kA
Rated breaking capacity to IEC 60947-2 (125V DC Icu)	
Rated breaking capacity to IEC 60947-2 (250V DC 2P in series Ics)	22 / 22 / 25kA
Frequency	50/60Hz
Trip Unit Type	PXR10
Continuous Current Range	320 - 800A
100% UL489 Rated	Yes
Instantaneous/Short Circuit Range	2 - 8 ln
Magnetic/Instantaneous Override	6800A
Dimensions H x W x D (inches)	16 x 8.25 x 4.38
Pole to pole distance inches	2,75
Approx Weight Ibs	29,98
RoHS Compliance	Yes
UL File Number	E7819
Ambient Temp Calibration	
Derating at 50C	
Derating at 60C	
Derating at 70C	

1. 480Vac corresponds to 277Vac for 1P

2. 600Vac corresponds to 347Vac for 1P

Part Number: PDG53K1200E3RNNNNNN



PRODUCT VIEW (Use Mouse to Rotate and Zoom)

Eaton's Power Defense<sup>™</sup> molded case circuit breakers, a globally rated platform designed to help keep your power system safe with latest protection technology. Engineered for the future: IoT and Industry 4.0 features such as built-in communications, advanced energy metering, and algorithms that signal breaker maintenance; zone selective interlock technology that clears faults quickly and locally; ArcFlash reduction options that help protect your people, and not to mention Eaton's best-inclass support and service.

### **Tech Data for Configured Product**

Power Defense Catalog Number	PDG53K1200E3RNNNNNN
Frame Size	Frame 5
Poles	3 Pole
Voltage	480V AC
Interruption or Breaking Capacity ( Icu/Ics)	50kA
Continuous Current Rating (In)	1200A
Trip Unit Type	PXR20
Trip Unit Options 1	LSIG
Trip Unit Options 2	Relays
Indicating Accessories	None
Indicating Accessories Terminal	None
Tripping Accessories	None
Tripping Accessory Terminal	None
Tripping Accessory Voltage	None
Line Type Description	None
Line Conductor Options	N/A
Line Terminal Type	N/A
Load Type Description	None
Load Conductor Options	N/A
Load Terminal Type	N/A
Special Options - Type of Modification	None
Details	None
Additional Description	None

### Molded Case Circuit Breakers Power Defense ™ UL Global Series Part Number: PDG53K1200E3RNNNNNN



Datasheet creation date: 19/08/2019

### **Technical drawings**







### **General Technical Data**

Frame Rating (In)	1200A			
Reference Standard	UL489, CSA 22.2, IEC 60947-2 & GB			
Number of poles	3			
Neutral rating	-			
Interruption Rating Designator	K/M/N/P/T			
UL Interruption Rating to UL 489 (240Vac)	85 / 100 / 150 / 200 / 200kA			
UL Interruption Rating to UL 489 (480Vac)	50 / 65 / 85 / 100 / 150kA			
UL Interruption Rating to UL 489 (600Vac)	25 / 35 / 50 / 65 / 65kA			
UL Interruption Rating to UL 489 (125/250Vdc)				
UL Current Limiting	-			
Rated breaking capacity to IEC 60947-2 (220-240 Vac Icu)	85 / 100 / 150 / 200kA			
Rated breaking capacity to IEC 60947-2 (220-240 Vac Ics)	85 / 100 / 100 / 150kA			
Rated breaking capacity to IEC 60947-2 (380-415 Vac Icu)	50 / 70 / 70 / 100kA			
Rated breaking capacity to IEC 60947-2 (380-415 Vac Ics)	50 / 50 /50 /50kA			
Rated breaking capacity to IEC 60947-2 (440 Vac Icu)	35 / 50 / 70 / 100kA			
Rated breaking capacity to IEC 60947-2 (440 Vac Ics)	35 / 40 / 50 / 50kA			
Rated breaking capacity to IEC 60947-2 (525 Vac Icu)	25 / 30 / 35 / 40kA			
Rated breaking capacity to IEC 60947-2 (525 Vac Ics)	20 /25 / 25 / 25kA			
Rated breaking capacity to IEC 60947-2 (690 Vac Icu)	10 / 15 / 20 / 35kA			
Rated breaking capacity to IEC 60947-2 (690 Vac Ics)	5 / 7.5 / 10 / 18kA			
Rated breaking capacity to IEC 60947-2 (125V DC Icu)				
Rated breaking capacity to IEC 60947-2 (250V DC 2P in series Ics)	25			
Frequency	50/60Hz			
Trip Unit Type	PXR20			
Continuous Current Range	500 - 1200A			
100% UL489 Rated	Yes			
Instantaneous/Short Circuit Range	2 - 10 ln			
Magnetic/Instantaneous Override	14400A			
Dimensions H x W x D (inches)	16 x 8.25 x 5.5			
Pole to pole distance inches	2,75			
Approx Weight Ibs	45			
RoHS Compliance	Yes			
UL File Number	E7819			
Ambient Temp Calibration				
Derating at 50C				
Derating at 60C				
Derating at 70C				

1. 480Vac corresponds to 277Vac for 1P

2. 600Vac corresponds to 347Vac for 1P

### **Specifications**

- Waterproof, shock-and vibration-resistant aluminum construction
- Saltwater tested and fully corrosion-resistant
- Short circuit, reverse polarity, and ignition protected
- For use with 12V/6 cell batteries that are flooded/wet cell, maintenance free or starved electrolyte (AGM) only
- FCC compliant
- UL listed to marine standard 1236
- 3 year warranty
- Replaces all existing current on-board chargers (excluding portables)
- No Price Increase
- Availability: November 2010



mmingora

DIGITAL LINEAR ON-BOARD CHARGERS				
PRODUCT	PRODUCT			
CODE	DESCRIPTION			
1821065	MK 106D (1 bank x 6 amps)			
1821105	MK-110D (1 bank x 10 amps)			
<mark>1822105</mark>	MK-210D (2 bank x 5 amps)			
1823155	MK-315D (3 bank x 5 amps)			
1822205	MK-220D (2 bank x 10 amps)			
1823305	MK-330D (3 bank x 10 amps)			
1824405	MK-440D (4 bank x 10 amps)			
1822305	MK-230D (2 bank x 15 amps)			
1823455	MK-345D (3 bank x 15 amps)			
1824605	MK-460D (4 bank x 15 amps)			







## **Digital Linear Chargers**

### Specifications (cont.)

New 4-color package design

minner

### **ON-BOARD MARINE BATTERY CHARGER**

DIGITALLY CONTROLLED 2X FASTER CHARGING PROTECTS BATTERIES



MK 2100 2 Charging Banks 5 AMPS PER Bank 10 AMPS TOTAL OUTPUT

minnkotamotors.com

# <sup>™</sup> <sup>™</sup> 10<sub>AMPS</sub>

# CHARGING TECHNOLOGY

#### DIGITALLY CONTROLLED.

Microprocessor design protects your batteries so you can stay on the water longer. It monitors temperature and state of charge to create a faster, regulated, more precise charge. Also includes automatic shut-off when charging is complete to extend battery life.

#### DIGITALLY CONTROLLED.

Microprocessor design protects your batteries so you can stay on the water longer. It monitors temperature and state of charge to create a faster, regulated, more precise charge. Also includes automatic shut-off when charging is complete to extend battery life.

#### ENHANCED STATUS CODES.

Provides comprehensive feedback on charge stage, maintenance mode status, error notification and full charge.

#### ENHANCED STATUS CODES.

Provides comprehensive feedback on charge stage, maintenance mode status, error notification and full charge.

minn faora



20 40 50 80 BATTERY TEMPERATURE (degree F)

#### MULTI-STAGE CHARGING.

Delivers a fast, precise charge profile by automatically controlling current and voltage without overcharging your batteries.

#### MULTI-STAGE CHARGING. Delivers a fast, precise charge profile by automatically controlling current and voltage without overcharging your batteries.

AUTOMATIC TEMPERATURE

#### COMPENSATION. Adjusts output voltage based on ambient temperature to ensure a full charge and protect your batteries.

N

AUTOMATIC TEMPERATURE COMPENSATION. Adjusts output voltage based on ambient temperature to ensure a full charce and protect your batteries.









